Overview



1. Volume Mute Button with LED
2. Volume Down Button
3. Volume Up Button
4. Stereo Speakers (2)
5. Integrated Optical Drive
6. 2 USB 2.0 Ports
7. Microphone Jack
8. Headphone Jack
9. Right Touchpad Button
10. Left Touchpad Button
11. Hard Drive Activity LED
12. Battery Charging LED
13. Power/Standby LED
14. Wireless On/Off LED
15. Touchpad with scroll zone
16. Power Button with LED
17. Wireless On/Off Button with LED

Overview



1. Kensington Lock Slot
2. RJ-45 Port (NIC)
3. RJ-11 Port (Modem)
4. IEEE 1394a Port
5. USB 2.0 Port
6. PC Card Slot
7. PC Card Eject Button
8. VGA/External Monitor Port
9. Power Connector

At A Glance

- Genuine Windows Vista Business 32,
  Genuine Windows Vista Home Basic 32,
  Genuine Windows XP Professional,
  Genuine Windows XP Home Edition,
  FreeDOS
- Sleek light-weight design starting at 5.6 lb (2.54 kg) and 1.2 inch (30 mm) thin at front
- 15.4-inch wide screen display with BrightView option
- Intel® Core™ 2 Duo processors, Intel Core Duo processors, Intel Core Solo processors, or Intel Celeron® M processors
- Mobile Intel 945GM Express Chipset or Mobile Intel 940GML Express Chipset
- Up to 4GB of 533- or 667-MHz DDR2 SDRAM, dual channel memory support*
- Intel Graphics Media Accelerator 950
- Up to 120-GB 5400 rpm, user-removable hard drive
- Optional LightScribe DVD+/-RW Drive with Double Layer
- Optional 802.11 a/b/g or 802.11 b/g wireless LAN modules and optional Bluetooth®
- IEEE 1394a Port
- Protected by a one-year standard parts and labor warranty – certain restrictions and exclusions apply.

* Memory greater than 2 GB requires Mobile Intel 945GM Express Chipset. Above 3-GB, all memory may not be available due to system resource requirements. 667-MHz memory is supported at a maximum speed of 533 MHz by the 940GML Express Chipset.

Standard Features

Processors

Intel Core 2 Duo Processor T7600 (2.33-GHz, 667-FSB, 4-MB L2 cache)*
Intel Core 2 Duo Processor T7400 (2.16-GHz, 667-FSB, 4-MB L2 cache)*
Intel Core 2 Duo Processor T7200 (2.0-GHz, 667-FSB, 4-MB L2 cache)*
Intel Core 2 Duo Processor T5600 (1.83-GHz, 667-FSB, 2-MB L2 cache)*
Intel Core 2 Duo Processor T5500 (1.66-GHz, 667-FSB, 2-MB L2 cache)*
Intel Core Duo processor T2600* (2.16-GHz, 667-MHz FSB, 2-MB L2 cache)
Intel Core Duo processor T2500* (2.00-GHz, 667-MHz FSB, 2-MB L2 cache)
Intel Core Duo processor T2400* (1.83-GHz, 667-MHz FSB, 2-MB L2 cache)
Intel Core Duo processor T2300* (1.66-GHz, 667-MHz FSB, 2-MB L2 cache)
Intel Core Duo processor T2300E* (1.66-GHz, 667-MHz FSB, 2-MB L2 cache)
Intel Core Duo Processor T2250* (1.73-GHz, 533-MHz FSB, 2-MB L2 cache) (select countries only)
Intel Core Duo Processor T2050* (1.60-GHz, 533-MHz FSB, 2-MB L2 cache) (select countries only)
Intel Core Solo Processor T1350* (1.86-GHz, 533-MHz FSB, 2-MB L2 cache) (select countries only)
Intel Core Solo Processor T1300* (1.66-GHz, 667-MHz FSB, 2-MB L2 cache)
Intel Celeron M Processor 450* (2.0-GHz, 533-MHz FSB, 1-MB L2 cache)
Intel Celeron M Processor 440* (1.86-GHz, 533-MHz FSB, 1-MB L2 cache)
Intel Celeron M Processor 430* (1.73-GHz, 533-MHz FSB, 1-MB L2 cache)
Intel Celeron M Processor 420* (1.60-GHz, 533-MHz FSB, 1-MB L2 cache)
Intel Celeron M Processor 410* (1.46-GHz, 533-MHz FSB, 1-MB L2 cache)

* Intel's numbering is not a measurement of higher performance.

NOTE: Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

Operating System

Preinstalled
Genuine Windows Vista Business 32*
Genuine Windows Vista Home Basic 32*
Genuine Windows XP Professional SP2
Genuine Windows XP Home Edition SP2
FreeDOS

Supported
(select drivers available on http://www.hp.com)
Genuine Windows Vista Business 64*†
Genuine Windows Vista Enterprise 32/64*†
Genuine Windows 2000

† 64-bit versions for Intel Core 2 Duo models only

Certified
SuSE Linux Enterprise Desktop 10

* Certain Windows Vista product features require advanced or additional hardware. See http://www.microsoft.com/windowsvista/getready/hardwarereqs.mspx and http://www.microsoft.com/windowsvista/getready/capable.mspx for details. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit http://www.windowsvista.com/upgradeadvisor.

Chipset

Mobile Intel 945GM Express Chipset with 667-MHz front side bus
or
Mobile Intel 940GML Express Chipset with 533-MHz front side bus

---

Standard Features

Graphics		Intel Graphics Media Accelerator 950 with up to 224-MB shared system memory Microsoft DirectX 9 capable
Display	**Internal**	15.4-inch WXGA display with 1280 x 800 resolution and 16M colors 15.4-inch WXGA BrightView display with 1280 x 800 resolution and 16M colors 15.4-inch WSXGA+ wide viewing angle display with 1680 x 1050 resolution and 16M colors
	External	Up to 32-bit per pixel color depth **VGA** port supports resolutions up to 2048 x 1536 at 75 Hz, and lower resolutions at up to 100 Hz **NOTE:** Resolutions are dependent upon monitor capability, and resolution and color depth settings.
Memory	**Standard**	256-MB, 512-MB, or 1024-MB 533-MHz or 667-MHz* DDR2 SDRAM SODIMMs; two SODIMM slots supporting dual channel memory
	Maximum	Supports up to 4096-MB maximum (2048-MB 667-MHz SODIMM in slots 1 and 2; requires Mobile Intel 945GM Express Chipset)
	Dual-channel	Maximized dual-channel performance requires SODIMMs of the same size and speed in both memory slots.
	* 667-MHz memory is supported at a maximum speed of 533 MHz by the Mobile Intel 940GML Express Chipset. **NOTE:** Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed. Above 3-GB, all memory may not be available due to system resource requirements.	
Communications		Integrated Broadcom 10/100 Ethernet PCI Controller 56K V.92 modem* with digital line guard * Designed for downloads from 56K modem compliant sources. Maximum achievable download transmission rates currently do not reach 56 KB/s, and will vary with line conditions. Modem availability is subject to country regulatory approval.
Wireless Devices		Support for a broad range of secure, integrated wireless LAN options featuring support for the latest industry standards. Integrated Bluetooth is also an option (factory configurable only) and can be combined with any one of the supported wireless LAN options.
	All integrated wireless LAN options	Wi-Fi certified Cisco Compatible Extensions support (Version 4.0) Wired Equivalent Privacy (WEP) support up to 128-bit keys Wi-Fi Protected Access (WPA) and WPA2 support 802.1x authentication support, including EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, and LEAP Advanced Encryption Standard (AES) support WiFi Certified for WPA2, WMM Dual antennas integrated in the display enclosure
	Intel PRO/Wireless 3945ABG Network Connection	Intel Centrino mobile technology Integrated support for 802.11a, b and g Up to 54-mbps data rate
	Intel PRO/Wireless 3945BG Network Connection	Intel Centrino mobile technology Integrated support for 802.11b and g Up to 54-mbps data rate

Standard Features

	Broadcom 4311AG WiFi Adapter	Integrated support for 802.11a, b and g Up to 54-mbps data rate
	Broadcom 4311BG WiFi Adapter	Integrated support for 802.11 b and g Up to 54-mbps data rate
	HP Integrated Module with Bluetooth 2.0 Wireless Technology	Bluetooth Specification v2.0 compliant Works with a wide range of Bluetooth devices
Keyboard	The 101/102-key compatible keyboard features an industry standard, full-pitch key layout with desktop keyboard features, such as the isolated inverted-T cursor control keys, editing keys, both left and right control and alt keys, and 12 function keys. US and International key layouts are available. Other features include an integrated numeric keypad, hotkeys for instant access to power conservation, brightness, and other features, 19-mm x 19-mm key pitch (center-to-center spacing), 2.5-mm stroke, comfort-dished keycaps, and bright key legends for improved visibility in low light conditions.	
One-Touch Productivity Buttons	Provide one-touch access to the following features: Wireless On/Off, Volume down, Volume up, and Volume Mute.	
Pointing Device	Touchpad with scroll zone and two soft-touch buttons	
Expansion Card Slots	**One Type I/II PC Card slot**	Supports 32-bit CardBus and 16-bit PC Cards
Storage	**Hard Drives**	40-, 60-, 80-, 100-, 120-GB 5400 rpm SMART SATA 100-GB 7200 rpm SMART SATA
	NOTE: These hard drives are customer removable and will withstand multiple insertion/removal cycles. Up to 8 GB is reserved for the system recovery software.	
	HP Mobile Data Protection System	Hard drive is mounted directly to the notebook frame, reducing the transmission of shock to the hard drive and protecting it during normal use from shock and vibration.
	Fixed Optical Drives	CD-ROM DVD-ROM DVD/CD-RW Combo DVD+/-RW SuperMulti with Double Layer LightScribe DVD+/-RW with Double Layer

Standard Features

Interfaces	**PC Card Slot**	One - Type I/II
	External Monitor	One – VGA
	IEEE 1394a Port	One
	External Microphone	One
	Headphone/Line out	One
	Power Connector	One
	RJ-11 (Modem)	One
	RJ-45 (NIC)	One
	USB 2.0	Three
	Accessory Battery Connector	One
	LED Status Indicators	Nine

Audio

PremierSound audio/speaker subsystem
ADI1981HD High Definition CODEC
Integrated 16-bit Sound Blaster Pro compatible audio
24-bit DAC
Integrated stereo speakers
External volume up, volume down, and mute buttons
Stereo headphone/line out
Stereo microphone in

Software

Preinstalled Software with Windows Vista or Windows XP

Adobe Acrobat Reader
HP Backup and Recovery Manager
HP Help and Support Center
HP Mobile Print Driver (Windows XP models)
HP ProtectTools Security Manager:
- BIOS Configuration for HP ProtectTools
- Credential Manager for HP ProtectTools

HP Quick Launch Buttons
HP Wireless Assistant
Sonic Digital Media Plus (Windows XP models):
- RecordNow! (for optional DVD+/-RW and DVD/CDRW drives)
- MyDVD (DVD Authoring for optional DVD+/-RW drives)

Roxio Creator 9 (Window Vista models with optional DVD+/-RW or DVD/CDRW drives)
Synaptics Touchpad Driver
Symantec Norton Internet Security with complimentary 60-day live update
Intervideo WinDVD - DVD Player (for optional DVD+/-RW, DVD/CDRW and DVD drives)

Additional software available from the Web

Smart Card Security for HP ProtectTools
Device Access Manager for HP ProtectTools

HP Backup and Recovery Manager

Each unit is shipped with HP Backup and Recovery Manager. HP Backup and Recovery Manager can provide data and system file protection for HP business PCs to enable fast recovery if the system becomes corrupted or if important information is accidentally deleted. HP Backup and Recovery Manager can perform scheduled or manual backups of the entire drive or individual files and folders. Up to 8 GB is reserved for the system recovery software. HP Backup and Recovery Manager can also create software recovery CDs or DVDs (requires optional hardware).

Standard Features

SMBIOS Version 2.4	System Management BIOS, previously known as DMI BIOS, is used to store system management information.
HP ProtectTools Security Manager	HP ProtectTools Security Manager is the security platform for business notebooks and desktops. The HP ProtectTools Security Manager is an extensible client security console that delivers enhanced security capabilities through add-on software modules. Modules currently available or planned are: - BIOS Configuration for HP ProtectTools - Credential Manager for HP ProtectTools - Device Access Manager for HP ProtectTools

Security	**Standard Features**	HP ProtectTools Security Manager Configuration Control Hardware Memory Change Alert Ownership Tag Setup Password Power-On Password DriveLock HP Disk Sanitizer Kensington Lock Slot Support for Computrace / LoJack for Laptops (must be purchased separately)

For more information on HP security solutions refer to http://www.hp.com/go/security.

Power Supply	External 65-watt AC adapter, 6-foot (1.8-meter) power cord included. Total length including External AC adapter is 12 feet (3.66 meter). HP Fast Charge Technology*

*Fast Charge Technology recharges your battery up to 90% within 90 minutes when the system is off. Fast Charge Technology does not apply to 12-cell Ultra-Capacity batteries.

Battery	**Primary Battery**	8-cell (69Wh) high capacity Lithium-Ion 6-cell (43Wh) high capacity Lithium-Ion
	Optional 8-Cell Extended Life Battery	8-cell (52Wh) high capacity Lithium-Ion
	Optional HP 12-Cell Ultra-Capacity Battery	12-cell (95Wh) high capacity Lithium-Ion

Standard Features

Battery Life		**8-cell (69Wh) Primary**	**6-cell (43Wh) Primary**
	Primary Battery	Up to 5 hours and 45 minutes	Up to 3 hours and 30 minutes
	Primary Battery and optional HP 8-Cell Extended Life Battery	Up to 9 hours and 45 minutes	Up to 7 hours and 30 minutes
	Primary Battery and optional HP 12-Cell Ultra-Capacity Battery	Up to 13 hours and 30 minutes	Up to 12 hours
	NOTE: Battery life will vary depending on the product configuration, product model, applications loaded on the product, power management settings of the product, and the product features used by the customer. As with all batteries, the maximum capacity of this battery will decrease with time and usage.		
System Standby Time	Up to 1 week		

Power Conservation	Supports enhanced Intel SpeedStep technology (allows Battery Optimized Mode, Maximum Performance Mode, or Automatic mode) Hibernation Standby ACPI compliance

Service and Support	HP Services includes a one-year standard parts and labor warranty, pick-up or carry-in, and toll-free 7 x 24 hardware technical phone support (depending on model). On-site service and warranty upgrades are also available. **NOTE:** Certain restrictions and exclusions apply. Consult the HP Customer Support Center for details. http://h20000.www2.hp.com/bizsupport/TechSupport/ProductRoot.jsp.

Options

Memory	256-MB 533-MHz DDR2 SDRAM	PE830A
	512-MB 533-MHz DDR2 SDRAM	PE831A
	1-GB 533-MHz DDR2 SDRAM	PE832A
	512-MB 667-MHz DDR2 SDRAM*	EM993AA
	1-GB 667-MHz DDR2 SDRAM*	EM994AA
	2-GB 667-MHz DDR2 SDRAM*	EM995AA
	* 667-MHz memory is supported at a maximum speed of 533 MHz by the Mobile Intel 940GML Express Chipset.	
MultiBay II Storage (9.5-mm) **NOTE:** Requires HP External MultiBay II	DVD-ROM MultiBay II Drive	PA849A
	Combo DVD/CD-RW MultiBay II Drive	PA850A
	DVD+/-RW Dual Format MultiBay II Drive	PA851A
	80-GB 5400 rpm MultiBay II Hard Drive	PH357A
Other Storage	80-GB 5400 rpm Primary SATA Hard Drive	ET354AA
	DVD+/-RW Double Layer Drive with LightScribe Upgrade	ET353AA
	HP USB Digital Drive + 256-MB Secure Digital Card	DL702AA
	HP USB Diskette Drive	DC361B
Communications	Intel PRO/Wireless 3945ABG 802.11 a/b/g WLAN option kit	EX150AA#xxx
Expansion Solutions	HP Monitor Stand	PA507A
	HP Adjustable Notebook Stand	PA508A
	HP External MultiBay II (9.5-mm)	PA509A#xxx
	HP 4-port USB 2.0 Hub	DG954A
Power	HP 2-bay Battery Charging Station	DT533A#xxx
	HP 10-bay Battery Charging Station	DT534A#ABA
	Battery Adapter kit #1	PK402A
	65W Smart AC Adapter	ED494AA#xxx
	90W Smart AC Adapter	ED495AA#xxx
	90W Smart Auto Adapter	ED493AA
	65W Air/Auto/AC Combo Adapter	ED993AA#xxx
	Primary 8-cell Battery Pack	PB992A
	HP 8-cell Extended Life Battery	PB993A
	HP 12-cell Ultra-Capacity Battery	EJ092AA
Carrying Cases	HP Entry Value Case	DL617A
	HP Top Load Nylon Case	DC915A
	HP Executive Leather Case	PA847A
	HP Sport Backpack	DG102A

Options

Security	HP PCMCIA Smart Card Reader	DC350B
	HP/Kensington Cable Lock	PC766A
Input/Output Devices	USB/PS2 Keyboard	DC852A#xxx
	USB/PS2 Optical Mouse	DC369A
	HP USB Optical Travel Mouse	F2100A

Memory

Supports up to 4096 MB* of 533-MHz or 667-MHz** DDR2 SDRAM
Two DIMM slots
DIMM sizes supported: 256 MB, 512 MB, 1024 MB, and 2048 MB

Standard Memory

- 256 MB (256 MB x 1)
- 512 MB (512 MB x 1 or 256 MB x 2)
- 1024 MB (1024 MB x 1 or 512 MB x 2)
- 2048 MB (1024 MB x 2)

Optional Memory Upgrades

Support for up to 4096 MB* of memory is available (with the installation of optional DDR2 SDRAM memory kits). Both memory slots are user accessible. Please refer to the Hardware and Software Guide for installation procedures. Maximized dual-channel performance requires SODIMMs of the same size and speed in both memory slots.

Up to	Slot 1	Slot 2
768 MB	512 MB	256 MB
1024 MB	1024 MB	Empty
1024 MB	512 MB	512 MB
1280 MB	1024 MB	256 MB
1536 MB	1024 MB	512 MB
2048 MB	1024 MB	1024 MB
4096 MB*	2048 MB	2048 MB

NOTE: This chart does not represent all possible memory configurations. Due to the non-industry standard nature of some third-party memory modules, we strongly recommend using only HP branded memory modules to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

Memory Upgrades

256-MB 533-MHz DDR2 SDRAM	PE830A
512-MB 533-MHz DDR2 SDRAM	PE831A
1024-MB 533-MHz DDR2 SDRAM	PE832A
512-MB 667-MHz DDR2 SDRAM	EM993AA
1024-MB 667-MHz DDR2 SDRAM	EM994AA
2048-MB 667-MHz DDR2 SDRAM	EM995AA

* Memory greater than 2 GB requires Mobile Intel 945GM Express Chipset. Above 3-GB, all memory may not be available due to system resource requirements.
** 667-MHz memory is supported at a maximum speed of 533 MHz by the Mobile Intel 940GML Express Chipset.

Removable Media Drive Support

	Quantity Supported	Drive Bay
LightScribe DVD+/-RW Drive with Double Layer	One	Fixed optical drive bay
DVD+/-RW SuperMulti Drive with Double Layer	One	Fixed optical drive bay
DVD/CD-RW Combo Drive	One	Fixed optical drive bay
DVD-ROM Drive	One	Fixed optical drive bay

Hard Drive Support

	Quantity Supported	Drive Bay
Primary Hard Drives		
100-GB 7200 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay
120-GB 5400 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay
100-GB 5400 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay
80-GB 5400 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay
60-GB 5400 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay
40-GB 5400 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay

Technical Specifications

System Unit	**Dimensions** (HxWxD)	1.2 in (at front) x 14.1 in x 10.2 in 30 mm (at front) x 357 mm x 260 mm	
	Weight	5.6 lb (2.54 kg)	
	NOTE: Height varies depending upon where on the notebook the measurement is made. Weight includes 6-cell battery, 60-GB hard drive, 512-MB memory, 802.11 wireless communications module. Weight varies by configuration and components.		
	Stand-Alone Power Requirements	Normal Operating Voltage	19 V
		Average Operating Power	25 W
		Max Operating Power	< 65 W
	Temperature	Operating	32° to 95° F (0° to 35° C) (not writing optical)
			41° to 95° F (5° to 35° C) (writing optical)
		Non-operating	-4° to 140° F (-20° to 60° C)
	Relative Humidity	Operating	10% to 90%, non-condensing
		Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
	Shock	Operating	125 G, 2 ms, half-sine
		Non-operating	200 G, 2 ms, half-sine
	Random Vibration	Operating	0.75 grms
		Non-operating	1.50 grms
	Altitude (unpressurized)	Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
		Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
	Industry Standard Certifications	Blue Angel	No
		UL	Yes
		CSA	Yes
		FCC Compliance	Yes
		Energy Star Compliant	Yes
		ICES	Yes
		GS	Yes
		Australia / NZ A-Tick Compliance	Yes
		CCC	Yes
		Japan VCCI Compliance	Yes
		MIC	Yes
		BSMI	Yes
		CE Marking Compliance	Yes
		BNCI or BELUS	Yes
		CIT	Yes
		GOST	Yes
		Saudi Arabian Compliance (ICCP)	Yes
		SABS	Yes
		UKRSERTCOMPUTER	Yes

Technical Specifications

HP 65W Smart AC Adapter	**Dimensions**	4.17 x 1.85 x 1.1 in (10.6 x 4.7 x 2.8 cm)	
	Weight	0.62 lb (280 g)	
	Input	100 to 240 VAC	
		Input Efficiency	83% min at 115 VAC
		Input frequency range	47 to 63 Hz
		Input AC current	1.7 A at 90 VAC, 0.85 A at 180 VAC
	Output	Output power 65W	65W
		DC output	18.5V
		Hold-up time	5 msec at 115 VAC input
		Output current limit	<11A, Over voltage protection- 29V max automatic shutdown
	Connector	3 pin/grounded, mates with interchangeable cords	
	Environmental Design	Operating temperature	32° to 104° F (0° to 40° C)
		Non-operating (storage) temperature	-4° to 149° F (-20° to 65° C)
		Altitude	0 to 10,000 ft (0 to 3,048 m)
		Humidity	20% to 80%
		Storage Humidity	10% to 90%
	EMI and Safety Certifications	CE Mark – full compliance with LVD and EMC directives; Worldwide safety standards – IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals – C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; MTBF – over 200,000 hours at 25°C ambient condition.	
	Option Kit Contents	65W AC Adapter, power cable, warranty booklet	

Optional HP 12-Cell Ultra-Capacity Battery	**Dimensions** (H x W x L)	1.3 x 6.0 x 10.6 in (3.33 x 15.25 x 26.88 cm)	
	Weight	1.77 lb (0.803 kg)	
	Cells/Type	12-cell Lithium-Ion	
	Energy	Voltage	14.8V
		Watt-hour Capacity	95Wh
		Amp-hour Capacity	6.45Ah
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)
		Operating (Discharging)	14° to 140° F (–10° to 60° C)
		Non-operating	–4° to 140° F (–20° to 60° C)
	Battery Re-Charge Time	Smart Adapter	3 to 4 hours
		System ON	4 to 5 hours (depending on system power consumption)
	Fuel Gauge	When pressed, LEDs light indicating level of charge remaining on battery	

Technical Specifications

Optional HP 8-Cell Extended Life Battery	**Dimensions** (H x W x L)	1.0 x 3.9 x 8.7 in (2.5 x 10.0 x 22.0 cm)	
	Weight	1.00 lb (0.455 kg)	
	Cells/Type	8-cell Lithium-Ion	
	Energy	Voltage	14.4V
		Watt-hour Capacity	52Wh
		Amp-hour Capacity	3.6Ah
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)
		Operating (Discharging)	14° to 140° F (–10° to 60° C)
		Non-operating	–4° to 140° F (–20° to 60° C)
	Battery Re-Charge Time	System in OFF mode or Standby	3 hours
		System ON	3 to 5 hours (depending on system power consumption)
		HP Fast Charge Technology	Charges the battery up to 90% within 90 minutes when system is OFF
	Fuel Gauge	When pressed, LEDs light indicating level of charge remaining on battery	

69Wh Primary 8-Cell Battery	**Dimensions** (H x W x L)	0.8 x 1.9 x 10.6 in (2.0 x 4.8 x 27.0 cm)	
	Weight	0.980 lb (0.445 kg)	
	Cells/Type	8-cell Lithium-Ion	
	Energy	Voltage	14.4V
		Watt-hour Capacity	69Wh
		Amp-hour Capacity	4.8Ah
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)
		Operating (Discharging)	14° to 140° F (-10° to 60° C)
		Non-operating	–4° to 140° F (–20° to 60° C)
	Battery Re-Charge Time	System in OFF Mode or Standby	2.5 hours
		System ON	3 to 5 hours (depending on system power consumption)
		HP Fast Charge Technology	Charges the battery up to 90% within 1.5 hours when system is OFF

Technical Specifications

43Wh Primary 6-Cell Battery	**Dimensions** (H x W x L)	0.8 x 1.9 x 10.6 in (2.0 x 4.8 x 27.0 cm)	
	Weight	0.74 lb (0.336 kg)	
	Cells/Type	6-cell Lithium-Ion	
	Energy	Voltage	10.8V
		Watt-hour Capacity	43Wh
		Amp-hour Capacity	4.0Ah
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)
		Operating (Discharging)	14° to 140° F (-10° to 60° C)
		Non-operating	–4° to 140° F (–20° to 60° C)
	Battery Re-Charge Time	System in OFF Mode or Standby	2.5 hours
		System ON	3 to 5 hours (depending on system power consumption)
		HP Fast Charge Technology	Charges the battery up to 90% within 1.5 hours when system is OFF

15.4-inch Color TFT WSXGA+ Wide Viewing Angle Display	**Active Area** (W x H)	13.0 x 8.1 in (33.1 x 20.7 cm)	
	Diagonal Size	15.4 in (39.1 cm)	
	Surface Treatment	Anti-glare	
	Number of Colors	Up to 16M	
	Contrast Ratio	300:1 (typical)	
	Refresh Rate	60 Hz	
	Brightness	170 nit (typical)	
	Pixel Resolution	**Pitch**	0.197 mm
		Format	1680 x 1050
		Configuration	RGB stripe
	Backlight	CCFL	
	PPI	129	
	Viewing Angle	±65° Horizontal, ± 50° Vertical (typical)	

15.4-inch Color TFT WXGA Display	**Active Area** (W x H)	13.0 x 8.1 in (33.1 x 20.7 cm)	
	Diagonal Size	15.4 in (39.1 cm)	
	Surface Treatment	Anti-glare	
	Number of Colors	Up to 16M	
	Contrast Ratio	300:1 (typical)	
	Refresh Rate	60 Hz	
	Brightness	170 nit (typical)	
	Pixel Resolution	**Pitch**	0.259 mm
		Format	1280 x 800
		Configuration	RGB stripe
	Backlight	CCFL	
	PPI	98	
	Viewing Angle	±45° Horizontal, ±25° Vertical (typical)	

Technical Specifications

15.4-inch Color TFT WXGA BrightView Display	**Active Area** (W x H)	13.0 x 8.1 in (33.1 x 20.7 cm)	
	Diagonal Size	15.4 in (39.1 cm)	
	Surface Treatment	BrightView	
	Number of Colors	Up to 16M	
	Contrast Ratio	300:1 (typical)	
	Refresh Rate	60 Hz	
	Brightness	170 nit (typical)	
	Pixel Resolution	**Pitch**	0.259 mm
		Format	1280 x 800
		Configuration	RGB stripe
	Backlight	CCFL	
	PPI	98	
	Viewing Angle	±45° Horizontal, ±25° Vertical (typical)	

Hard Drives

100-GB 7200 rpm SATA	**Drive Weight**	0.25 lb (113 g)	
	Capacity	100 GB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-7 / SATA 1.0a	
	Transfer Rate	Synchronous (maximum)	100 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	Single Track	1 ms
		Average	10 ms
		Maximum	18 ms
	Rotational Speed	7200 rpm	
	Logical Blocks	195,371,568	
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]	
	Features	ATA Security	

120-GB 5400 rpm SATA	**Drive Weight**	0.22 lb (101 g)	
	Capacity	120 GB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-7 / SATA 1.0a	
	Transfer Rate	Synchronous (maximum)	100 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	Single Track	3 ms
		Average	13ms
		Maximum	24 ms
	Rotational Speed	5400 rpm	
	Logical Blocks	234,441,648	
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]	
	Features	ATA Security	

Technical Specifications

100-GB 5400 rpm SATA	**Drive Weight**	0.22 lb (101 g)	
	Capacity	100 GB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-7 / SATA 1.0a	
	Transfer Rate	Synchronous (maximum)	100 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	Single Track	3 ms
		Average	13 ms
		Maximum	24 ms
	Rotational Speed	5400 rpm	
	Logical Blocks	195,371,568	
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]	
	Features	ATA Security	

80-GB 5400 rpm SATA	**Drive Weight**	0.22 lb (101 g)	
	Capacity	80 GB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-7 / SATA 1.0a	
	Transfer Rate	Synchronous (maximum)	100 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	Single Track	3 ms
		Average	13 ms
		Maximum	24 ms
	Rotational Speed	5400 rpm	
	Logical Blocks	156,301,488	
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]	
	Features	ATA Security	

60-GB 5400 rpm SATA	**Drive Weight**	0.22 lb (101 g)	
	Capacity	60 GB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-7 / SATA 1.0a	
	Transfer Rate	Synchronous (maximum)	100 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	Single Track	3 ms
		Average	13 ms
		Maximum	24 ms
	Rotational Speed	5400 rpm	
	Logical Blocks	117,231,408	
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]	
	Features	ATA Security	

Technical Specifications

40-GB 5400 rpm SATA	**Drive Weight**	0.22 lb (101 g)	
	Capacity	40 GB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-7 / SATA 1.0a	
	Transfer Rate	Synchronous (maximum)	100 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	Single Track	3 ms
		Average	13 ms
		Maximum	24 ms
	Rotational Speed	5400 rpm	
	Logical Blocks	78,165,360	
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]	
	Features	ATA Security	

Removable Storage Drives – Fixed Bay

CD-ROM Drive	**Access Times**	Random	<110 ms CD
	Max Data Transfer Rate	24X CD-ROM	3,600 KB/s
	Transfer Mode	Multiword DMA Mode 2	
	Interface	EIDE	
	Supported Media (read)	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW	
	Supported Media (write)	None	
	Max Media Capacity (read)	700 MB	
	Transport	Tray Loading	

DVD-ROM Drive	**Access Times**	Random	<116 ms CD
			<125 ms DVD
	Max Data Transfer Rate	24X CD-ROM	3,600 KB/s
		8X-DVD	10,800 KB/s
	Transfer Mode	Multiword DMA Mode 2	
	Interface	EIDE	
	Supported Media (read)	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW	
	Supported Media (write)	None	
	Max Media Capacity (read)	4.7 GB	
	Transport	Tray Loading	

Technical Specifications

DVD/CD-RW Combo Drive	**Access Times**	Random	<110 ms CD
			<130 ms DVD
	Max Data Transfer Rate	24X CD-ROM	3,600 KB/s
		8X DVD	10,800 KB/s
		24X CD-R	3,600 KB/s
		24X CD-RW	3,600 KB/s
	Transfer Mode	Multiword DMA Mode 2	
	Interface	EIDE	
	Supported Media (read)	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW	
	Supported Media (write)	CD-R, CD-RW	
	Max Media Capacity (read)	8.5 GB	
	Max Media Capacity (write)	700 MB	
	Transport	Tray loading	

LightScribe DVD+/-RW Drive with Double Layer	**Access Times**	Random	<175 ms CD
			<230 ms DVD
	Max Data Transfer Rate	24X CD-ROM	3,600 KB/s
		8X DVD	10,800 KB/s
		24X CD-R	3,600 KB/s
		16X CD-RW	2,400 KB/s
		8X DVD+R	10,800 KB/s
		4X DVD+RW	5,400 KB/s
		8X DVD-R	10,800 KB/s
		4X DVD-RW	5,400 KB/s
		2.4X DVD+R(9)	2,700 KB/s
	Transfer Mode	Multiword DMA Mode 2	
	Interface	EIDE	
	Supported Media (read)	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW	
	Supported Media (write)	CD-R, CD-RW, DVD+R, DVD+RW, DVD-R, DVD-RW, LightScribe	
	Max Media Capacity (read)	8.5 GB	
	Max Media Capacity (write)	8.5 GB	
	Transport	Tray Loading	

Technical Specifications

DVD+/-RW SuperMulti Drive with Double Layer	**Access Times**	Random	<175 ms CD
			<230 ms DVD
	Max Data Transfer Rate	24X CD-ROM	3,600 KB/s
		8X DVD	10,800 KB/s
		24X CD-R	3,600 KB/s
		16X CD-RW	2,400 KB/s
		8X DVD+R	10,800 KB/s
		4X DVD+RW	5,400 KB/s
		8X DVD-R	10,800 KB/s
		4X DVD-RW	5,400 KB/s
		2.4X DVD+R(9)	2,700 KB/s
		5X DVD-RAM	6,750 KB/s
	Transfer Mode	Multiword DMA Mode	
	Interface	EIDE	
	Supported Media (read)	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW, DVD-RAM	
	Supported Media (write)	CD-R, CD-RW, DVD+R, DVD+RW, DVD-R, DVD-RW, DVD-RAM	
	Max Media Capacity (read)	8.5 GB	
	Max Media Capacity (write)	8.5 GB	
	Transport	Tray Loading	

PremierSound Audio

Hardware	**Implementation**	ADI1981HD High Definition CODEC
	Volume Controls	Up, down, and mute buttons
	Full Duplex	Yes
	Sound Blaster Pro compatible	Yes
	Microphone Jack	Stereo or mono
	Headphone/Line Out Jack	Stereo

Audio Output Quality	**Frequency Response**	20 Hz – 20 kHz
	Signal to Noise Ratio	>85 dB
	Total Harmonic Distortion	0.01%
	Noise Floor	-110 dB
	Play/Record Sampling Rate(s)	8 kHZ – 48kHz
	DAC	16, 20 or 24-bit
	ADC	16 or 20-bit

Technical Specifications

Internal Speakers	**Power Rating**	2 Watts
	Impedance	4 Ohms

Communications

Integrated Broadcom 10/100 Ethernet PCI Controller (BCM4401)	**Ethernet Features**	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)
	Power Management	ACPI compliant -- multiple power modes Situation-sensitive features reduce power consumption
	Manageability	Wake-on-LAN from standby and hibernation (configurable; Magic Packet and Microsoft Wake-Up Frame) PXE 2.1 Remote Boot Statistics Gathering (RMON, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite
	Interface	32-bit PCI, 33-MHz
	NIC Device Driver Name	Broadcom 440X 10/100 Integrated Controller
	Drivers Available	Microsoft Windows XP Microsoft Windows 2000

V.92 56K Data/Fax Modem	**Form Factor**	MDC 1.5 Daughtercard
	Power Management Support	APM Revision 1.2, ACPI
	Approvals/ Certifications	UL, CSA, NEMKO, CCIB, Industry Canada, FCC Part 68, CTR21, FCC Part 15 Class B, Canadian ICES-003 Class B, C.I.S.P.R.22, Australian ACA, CE Mark, Other Countries
	Data Mode Capabilities	V.92 data V.8bis V.80 V44, V.42bis, MNP5 (Compression) V.42 (LAPM, MNP2-4) (Error Correction) **Optional symbol rates:** 2800, 3429 Asymmetric Symbol rates **Synchronous primary channel data signaling rates:** 3600, 31200 Automatic rate re-negotiation V.34 V.32bis V.32 V.23 V.22bis

		V.22 V.21 Bell 212A Bell 103J
	Fax Mode Capabilities	TIA/EIA-578-B (Class 1) T.30, T.4 (Group 3) V.17 V.29 V.27ter V.21 Channel 2
	Command Set	V.250 (Partial) TIA-602 Identification: +GMI, +GMM, +GMR Port control: +IPR, +ICF, +IFC, +ILRR Modulation: +MS, +MR, +MA Error control: +ES, +ER, +EB, +ESR, +ETBM Data compression: +DS, +DR V.251
Broadcom 4311BG 802.11b/g WiFi Adapter	**Wireless LAN Standards**	IEEE 802.11b IEEE 802.11g
	Interoperability	Wi-Fi certified Cisco Compatible Extensions Program compliant (details at www.hp.com/go/notebooks/WLAN)
	Frequency Band	2.4 GHz
	Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM
	Security[1]	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST, EAP-SIM. Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4).
	Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.
	Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK
	Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power (for CKK)[2]	17.5 dBm
	Output Power (for OFDM; power varies by data rate)[2]	15 dBm
	Power Consumption	Transmit: 2.0 W (max) Receive: 1.5 W (max) Idle mode[3]: 390 mW (nominal) Sleep mode: 20 mW (max)
	Power Management	ACPI compliant power management 802.11 compliant power saving mode

Technical Specifications

Receiver Sensitivity[4]	54 Mbps: -72 dBm, 11 Mbps: -88 dBm , 1 Mbps: -97 dBm	
Antenna type	High efficiency dual band antenna with spatial diversity, mounted in the display enclosure	
Range	802.11 b – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
	802.11 g – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
Form Factor	PCI-Express MiniCard	
Weight	0.026 lb (12 g)	
Dimensions	0.19 x 1.2 x 2.0 in (4.75 x 29.85 x 50.8 mm)	
Operating Voltage	3.3v +/- 10%	
Temperature	Operating Non-operating	32° to 176° F (0° to 80° C) -40° to 176° F (-40° to 80° C)
Humidity	Operating Non-operating	10% to 90% (non-condensing) 5% to 95% (non-condensing)
Altitude	Operating Non-operating	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)
Configuration Utility[5]	Choice of Configuration Utility: • Microsoft Windows XP Wireless Network Connection Manager • Broadcom Wireless Configuration Utility (required for Cisco Compatible Extensions support)	
LED Activity	LED Off – Radio OFF; Solid LED On – Radio ON	

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. In Power Save Polling mode.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
5. WLAN supplier's client utility is required for Cisco Compatible Extensions support. WLAN may also be compatible with certain third-party software supplicants.

Broadcom 4311AG 802.11a/b/g WiFi Adapter

Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g
Interoperability	Wi-Fi certified Cisco Compatible Extensions Program compliant (details at www.hp.com/go/notebooks/WLAN)
Frequency Band	2.4 GHz and 5 GHz
Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM
Security[1]	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST, EAP-SIM. Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4).
Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.
Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK

Technical Specifications

Network Architecture	Ad-hoc (Peer to Peer)	
Models	Infrastructure (Access Point Required)	
Roaming	IEEE 802.11 compliant roaming between access points	
Output Power (for CKK)[2]	17.5 dBm	
Output Power (for OFDM; power varies by data rate)[2]	15 dBm	
Power Consumption	Transmit: 2.0 W (max) Receive: 1.5 W (max) Idle mode[3]: 390 mW (nominal) Sleep mode: 20 mW (max)	
Power Management	ACPI compliant power management 802.11 compliant power saving mode	
Receiver Sensitivity[4]	54 Mbps: -72 dBm, 11 Mbps: -88 dBm , 1 Mbps: -97 dBm	
Antenna type	High efficiency dual band antenna with spatial diversity, mounted in the display enclosure	
Range	802.11 a – Typical (@6 Mbps)	600 feet – Outdoor Open Area 150 feet – Indoor, Office environment
	802.11 b – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
	802.11 g – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
Form Factor	PCI-Express MiniCard	
Weight	0.026 lb (12 g)	
Dimensions	0.19 x 1.2 x 2.0 in (4.75 x 29.85 x 50.8 mm)	
Operating Voltage	3.3v +/- 10%	
Temperature	Operating Non-operating	32° to 176° F (0° to 80° C) -40° to 176° F (-40° to 80° C)
Humidity	Operating Non-operating	10% to 90% (non-condensing) 5% to 95% (non-condensing)
Altitude	Operating Non-operating	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)
Configuration Utility[5]	Choice of Configuration Utility: • Microsoft Windows XP Wireless Network Connection Manager • Broadcom Wireless Configuration Utility (required for Cisco Compatible Extensions support)	
LED Activity	LED Off – Radio OFF; Solid LED On – Radio ON	

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. In Power Save Polling mode.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
5. WLAN supplier's client utility is required for Cisco Compatible Extensions support. WLAN may also be compatible with certain third-party software supplicants.

Intel PRO/Wireless 3945ABG 802.11a/b/g Network Connection	**Wireless LAN Standards**	IEEE 802.11a IEEE 802.11b IEEE 802.11g

Technical Specifications

Interoperability	Wi-Fi certified Cisco Compatible Extensions Program compliant (details at www.hp.com/go/notebooks/WLAN)	
Frequency Band	2.4 GHz and 5 GHz	
Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps	
Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM	
Security[1]	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST, EAP-SIM. Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4).	
Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.	
Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK	
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)	
Roaming	IEEE 802.11 compliant roaming between access points	
Output Power (for CKK)[2]	15 dBm	
Output Power (for OFDM; power varies by data rate)[2]	15 dBm	
Power Consumption	Transmit: 1.8 Watts (max) Receive: 1.4 Watts (max) Idle mode[3]: 150 mW (nominal) Sleep mode: 30 mW (max)	
Power Management	ACPI compliant power management 802.11 compliant power saving mode	
Receiver Sensitivity[4]	54 Mbps: -72 dBm, 11 Mbps: -88 dBm , 1 Mbps: -97 dBm	
Antenna type	High efficiency dual band antenna with spatial diversity, mounted in the display enclosure	
Range	802.11 a – Typical (@6 Mbps)	600 feet – Outdoor Open Area 150 feet – Indoor, Office environment
	802.11 b – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
	802.11 g – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
Form Factor	PCI-Express MiniCard	
Weight	0.013 lb (6 g)	
Dimensions	0.19 x 1.2 x 2.0 in (4.75 x 29.85 x 50.8 mm)	
Operating Voltage	3.3v +/- 10%	
Temperature	Operating Non-operating	32° to 176° F (0° to 80° C) -40° to 176° F (-40° to 80° C)
Humidity	Operating Non-operating	10% to 90% (non-condensing) 5% to 95% (non-condensing)
Altitude	Operating Non-operating	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)

	Configuration Utility[5]	Choice of Configuration Utility: • Microsoft Windows XP Wireless Network Connection Manager • Intel PROSet (required for Cisco Compatible Extensions support)
	LED Activity	LED Off – Radio OFF; Solid LED On – Radio ON

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. In Power Save Polling mode.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
5. WLAN supplier's client utility is required for Cisco Compatible Extensions support. WLAN may also be compatible with certain third-party software supplicants.

Intel PRO/Wireless 3945BG 802.11b/g Network Connection

	Wireless LAN Standards	IEEE 802.11b IEEE 802.11g
	Interoperability	Wi-Fi certified Cisco Compatible Extensions Program compliant (details at www.hp.com/go/notebooks/WLAN)
	Frequency Band	2.4 GHz
	Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM
	Security[1]	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST, EAP-SIM. Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4).
	Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.
	Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK
	Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power (for CKK)[2]	15 dBm
	Output Power (for OFDM; power varies by data rate)[2]	15 dBm
	Power Consumption	Transmit: 1.8 Watts (max) Receive: 1.4 Watts (max) Idle mode[3]: 150 mW (nominal) Sleep mode: 30 mW (max)
	Power Management	ACPI compliant power management 802.11 compliant power saving mode
	Receiver Sensitivity[4]	54 Mbps: -72 dBm, 11 Mbps: -88 dBm , 1 Mbps: -97 dBm
	Antenna type	High efficiency dual band antenna with spatial diversity, mounted in the display enclosure
	Range	802.11 b – Typical (@1 Mbps): 1200 feet – Outdoor Open Area; 300 feet – Indoor, Office environment

	802.11 g – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
Form Factor	PCI-Express MiniCard	
Weight	0.013 lb (6 g)	
Dimensions	0.19 x 1.2 x 2.0 in (4.75 x 29.85 x 50.8 mm)	
Operating Voltage	3.3v +/- 10%	
Temperature	Operating Non-operating	32° to 176° F (0° to 80° C) -40° to 176° F (-40° to 80° C)
Humidity	Operating Non-operating	10% to 90% (non-condensing) 5% to 95% (non-condensing)
Altitude	Operating Non-operating	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)
Configuration Utility[5]	Choice of Configuration Utility: • Microsoft Windows XP Wireless Network Connection Manager • Intel PROSet (required for Cisco Compatible Extensions support)	
LED Activity	LED Off – Radio OFF; Solid LED On – Radio ON	

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. In Power Save Polling mode.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
5. WLAN supplier's client utility is required for Cisco Compatible Extensions support. WLAN may also be compatible with certain third-party software supplicants.

HP Integrated Module with Bluetooth Wireless Technology	**Bluetooth Specification**	2.0 Compliant
	Dimensions	1.02 x 0.55 x 0.22 in (26 x 14 x 5.7 mm)
	Frequency Band	2402 to 2480 MHz
	Number of Available Channels	79 (1 MHz) available channels
	Data Rates and Throughput	3 Mbps data rate; throughput up to 2.17 Mbps Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric or 1306.9 kbps symmetric
	Transmit Power	-6 dBm to 4 dBm (Bluetooth Class II)
	Receiver Sensitivity	Better than -80 dBM at 0.1 % raw bit error rate
	Power Consumption	Peak (Tx) 264 mW Peak (Rx) 231 mW Sleep <1 mW
	Antenna	Internally integrated within module
	Range	Up 33 ft (10 m)
	Electrical Interface	USB 2.0 compliant Microsoft Windows Plug and Play compliant
	OS Support	Microsoft Windows XP Professional and Home Microsoft Windows 2000
	Bluetooth Software Supported	Broadcom Bluetooth for Windows Microsoft Windows XP Bluetooth Software
	Link Topology	Point to Point, Multipoint Pico Nets up to 7 slaves

Technical Specifications

Security	Full support of Bluetooth Security Provisions	
Power Management	Microsoft Windows ACPI, and USB Bus Support	
	Self configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff	
Certifications	All necessary regulatory approvals for supported countries, including:	
	FCC (47 CFR) Part 15C, Section 15.247 & 15.249	
	ETS 300 328, ETS 300 826	
	Low Voltage Directive IEC950	
	UL, CSA, and CE Mark	
Temperature	Operating	-4° to 158° F (-20° to 70° C)
	Non-operating	-40° to 176° F (-40° to 80° C)
Humidity	Operating	10% to 90%
	Non-operating	5% to 95%
Altitude	Operating	15,000 ft (4,572 m)
	Non-operating	40,000 ft (12,192 m)
Bluetooth Profiles Supported	(with Bluetooth for Windows 4.0 software)	
	Serial Port Profile (SPP)*	
	Dial-Up Networking (DUN)*	
	Generic Object Exchange Profile (GOEP)	
	Object Push Profile (OPP)*	
	File Transfer Profile (FTP)	
	Synchronization Profile (SYNC)	
	Hard Copy Cable Replacement (HCRP)*	
	Personal Area Networking Profile (PAN)*	
	Human Interface Device Profile (HID)*	
	FAX Profile (FAX)	
	Basic Imaging Profile (BIP)	
	Headset Profile (HSP)	
	Hands Free Profile (HFP)	
	Advanced Audio Distribution Profile (A2DP)	

* indicates the profile is also supported by Microsoft Windows XP SP2

Environmental Data	**Eco-Label Certifications**	This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: • US Energy Star • US Federal Energy Management Program (FEMP) • Taiwan Green Mark • China Energy Conservation Program • IT ECO declaration
	System Configuration	The configuration used for the Energy Consumption and Declared Noise Emissions data is based on a "Typically Configured Notebook."

Energy Consumption	115 VAC	230 VAC	100 VAC
Normal Operation	23 W	23.5 W	23 W
Sleep (Energy Star low power mode)	1.72 W	1.88 W	1.73 W
Off	1.90 W	1.98 W	1.90 W
Heat Dissipation*	**115 VAC**	**230 VAC**	**100 VAC**
Normal Operation	78.5 BTU/hr	80.2 BTU/hr	78.5 BTU/hr
Sleep	5.9 BTU/hr	6.4 BTU/hr	5.9 BTU/hr
Off	6.5 BTU/hr	6.8 BTU/hr	6.5 BTU/hr

***NOTE**: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

This product is in compliance with US executive order 13221, WOL (wake on LAN) disabled.

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
Idle	3.0	28.0
Fixed Disk (random writes)	3.9	33.8
Optical Drive (sequential reads)		34.0
	System fan is usually off except when charging the battery	
System Fan On		29.0
Idle		34.0
Fixed Disk (random writes)		42.0

Batteries

This product complies with ISO standards:

EU Directive 91/ 157/ EEC
EU Directive 93/ 86/ EEC
EU Directive 98/ 101/ EEC

Batteries used in the product do not contain:

Mercury greater than 5ppm by weight
Cadmium greater than 10ppm by weight
Lead greater than 4000 ppm by weight.

Battery type and chemistry used in the product:

Primary battery
6-cell high capacity Lithium-Ion battery pack

Real Time Clock battery
CR2032 (coin cell), Lithium

Additional Information

This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive – 2002/95/EC.

This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.

Keyboard complies with ISO standard: ISO 9995, EN 29241-4, and

ISO/IEC 15412

Input devices of this product comply with ISO 9241, part 9.

Plastics parts weighing over 0.055 pounds (25 grams) used in the product are marked per ISO 11469 and ISO1043.

This product contains 0% recycled materials (by wt.)

This product is greater than 85% recycle-able when properly disposed of at end of life.

Packaging

Packaging Materials

- External:
  - Corrugated Paper 920 g
- Internal:
  - EPE Foam 266 g
  - LDPE Bag 14 g
  - Corrugated/Paper 210 g
- The plastic packaging material is made from 0% recycled content.
- The corrugated paper packaging materials contains at least 80% recycled content.

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (for reference of these limits please refer to the HP General Specification of the Environment (http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface

designed to be frequently handled or carried by the user.

- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

End-of-life Management and Recycling	HP offers our customers several other options for handling their aging computers while also minimizing the impact on the environment-including product trade-in and leasing services-in addition to recycling services. Please go to: http://www.hp.com/recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.
Hewlett-Packard Corporate Environmental Information	For more information about HP's commitment to the environment: Global Citizenship Report http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html Environment website http://www.hp.com/environment Eco-label certifications http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html ISO 14001 certificates: http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html

Copyright © 2007 Hewlett-Packard Development Company, L.P.

All rights reserved. Microsoft, Windows, Windows Vista, and Windows XP are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. Core Duo, Centrino, and SpeedStep are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth is a registered trademark of Bluetooth SIG, Inc., in the U.S. and other countries. All other product names mentioned herein may be trademarks of their respective companies.

The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.